


Technical data sheet

Lightning current arrestor, 3-pole + NPE with function display



LightningController-Set, 4-pole, with visual function display, for use in TN-S and TT networks:

Completely pre-terminated and ready for connection, consisting of:
MC 50-B-OS: Lightning current arrestor, Type 1 (Class B) to EN
61643-11 for interface O to 1 (LPZ) according to lightning protection
zone concept to IEC 61313-1 and DIN VDE 0185-305.
MC 125-B/NPE: N-PE spark gap, Type 1 (Class B) to IEC 61643 for
use in TN-S and TT systems.



230 /
400 V
System Type
1 LPZ
0 → 1 CE 5




- Conforms to VDN directive 2nd Edition 2004
- Cover and base, plug-in cover
- Arresting capacity 50 kA (10/350 µs) per pole
- Voltage protection level • Power consumption • Line follow current quenching 25 kA Ipeak
- Incl. plug caps for identifying the connections
- Encapsulated, non-extinguishing spark gap: Can be used in standard distributor housings

Note: Requires a total of 5 m cable length as a decoupling length for surge protection.

Type	Maximum continuous voltage V	Version	Pack Units	Weight kg/100 pc.	Art.-No.
MC 50-B 3+1-OS	255	3 + NPE	1	170.000	5096832

G /pc.

Connection-/Circuit diagram



Article number	5096832		
Nominal voltage	U_N	V	230
SPD to EN 61643-11	Type 1		
SPD to IEC 61643-1	class I		
LPZ	0/1		
Lightning impulse current (10/350)	I_{imp}	kA	50
Nominal discharge surge current (8/20)	I_n	kA	50
Arrester surge current (8/20) [total]		kA	125
Voltage protection level	U_p	kV	< 2,0
Response time	t_A	ns	<100
Follow current quenching capacity I_{peak}	$I_{fi\ peak}$	kA	25
Maximum back-up fuse		A	500
Temperature range	?	°C	-40
Division unit TE (17.5 mm)			8
Protection rating			IP 20
Connection cross-section, rigid		mm ²	10
Connection cross-section, multi-wire		mm ²	10
Connection cross-section, flexible		mm ²	10

Legend

 230/400 V-system

 Protection device to DIN EN 61643-11 or IEC 61643-11

 Transition from LPZ 0 to LPZ 1

 Communautés Européennes, EC declaration of conformity according to EC directives

 5-year warranty