

JUMO GmbH & Co. KG
Delivery address: Mackenrodtstraße 14,
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
E-mail: mail@jumo.net
Internet: www.jumo.net

JUMO Instrument Co. Ltd.
JUMO House
Temple Bank, Riverway
Harlow - Essex CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 63 52 62
E-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.
8 Technology Boulevard
Canastota, NY 13032, USA
Phone: 315-697-JUMO
1-800-554-JUMO
Fax: 315-697-5867
E-mail: info@jumo.us
Internet: www.jumo.us



RTD temperature probes for the food and pharmaceutical industries

- for temperatures from -50 to +250 °C
- EHEDG certification
- stainless steel protection tubes
- with optional 2-wire transmitter
- CIP-compliant installation


The RTD temperature probes can optionally be provided with terminal heads in stainless steel, aluminium die-casting, or plastic.

To suit the specific needs of the different sectors of the food and pharmaceutical industries, a wide variety of process connections can be supplied: from G 1/2 (1/2" pipe) screw fittings with CIP-compliant sealing cone, through taper nipples with ring nut (milke pipe fitting), and clamping nipples, to sliding ball weld-in sockets, weld-in sockets, Varivent connections, and ball weld-in pockets. The protection tubes are made from stainless steel.

The RTD temperature probes for the food and pharmaceutical industries are suitable for the temperature range from -50 to +250 °C.

Pt100 single and twin temperature sensors to EN 60751, Class A, in 3-wire circuit ensure the highest degree of accuracy.

For longer transmission distances, analog or programmable 2-wire transmitters are optionally available.



Technical data

Terminal head

stainless steel 1.4571, M 16x1.5; IP67, ambient temperature -20 to +100 °C
Form B DIN 43729, aluminium die-casting, M 20x1.5; IP54, ambient temperature -40 to +100 °C
Form BUZ, aluminium die-casting, M 20x1.5; IP65, ambient temperature -40 to +100 °C
Form BUZH, aluminium die-casting, M 20x1.5; IP65, ambient temperature -40 to +100 °C
Form BBKS, plastic (PA 6), M 20x1.5; IP54, ambient temperature -30 to +130 °C
Caution: reduced ambient temperature when using transmitters;
data sheet 70.7010/70.7030

Extension tube

stainless steel, approx. 70 mm long, 9 mm dia.

Process connection

screw fitting with CIP-compliant sealing cone, stainless steel 316 L, with EHEDG certification
clamping nipple to DIN 32676, stainless steel 316 L
clamping nipple with ring nut (milk pipe fitting) to DIN 11851, stainless steel 316 L
ball weld-in socket, stainless steel 316 L, clamping ring in PTFE
CIP-compliant weld-in socket, stainless steel 316 L, seal in PTFE
Varivent connection, stainless steel 316 L, with EHEDG certification
ball weld-in pocket, stainless steel 316 Ti
JUMO PEKA process connection adapter, stainless steel 316 L, with EHEDG certification

Sheath

stainless steel 316 L, 6 mm dia.
stainless steel 316 Ti, on request

Measuring insert

Pt100 temperature sensor to EN 60751, Class A, 3-wire circuit

Response times

$t_{0,9} = 10$ sec, in water 0.4 m/sec, 6 mm dia.

Transmitter

analog transmitter, output 4 to 20 mA, data sheet 70.7030
analog transmitter, output 0 to 10 V, data sheet 70.7030
programmable transmitter, output 4 to 20mA/20 to 4 mA, data sheet 70.7010

Approval/approval marks



JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14,
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow - Essex CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 63 52 62
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk


JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-JUMO
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info@jumo.us
 Internet: www.jumo.us



Dimensions



Possible variants

Screw fitting with
 CIP-compliant conical seal





Clamping nipple to DIN 32676

DN	D1	DN	D1
-	Ø25	40/1,5"	Ø50,5
10/20	Ø34	50/2"	Ø64
25/1"	Ø50,5	2,5"	Ø77,5



Stainless steel
 terminal head KGI-1



Ball weld-in socket
 with clamping thread



Aluminium die-casting
 terminal head Form B



Taper nipple with ring nut
 to DIN 11851
 (milk pipe fitting)

DN	D1	D2	D3	D4	L1	L2
10	Ø22	Ø18	RD 28x1/8	Ø38	9	18
25	Ø44	Ø35	RD 52x1/8	Ø63	13	21
32	Ø50	Ø41	RD 58x1/8	Ø70		



Plastic
 terminal head Form BBKS


Weld-in socket
 with CIP-compliant sealing system





Aluminium die-casting
 terminal head Form BUZ

Varivent connection

DN	D1
15/10	Ø31
32/25	Ø50
50/40	Ø68




Ball weld-in pocket



Aluminium die-casting
 terminal head Form BUZH

JUMO PEKA
 Process connection adapter
 as per data sheet 40,9711

Varivent	Clamp	Aseptic	Weld-in socket
DN 25/32	DN 25/32/40	DN 40	Ø 55 mm
DN 40-125	DN 50	DN 50	
		NKS DN 40	



JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14,
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow - Essex CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 63 52 62
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-JUMO
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info@jumo.us
 Internet: www.jumo.us




Order details: RTD temperature probes for the food and pharmaceutical industries

(1) Basic type

902810/13	RTD temperature probes with terminal head Form B
-----------	--

902810/20	RTD temperature probes with terminal head in stainless steel
-----------	--



(2) Measuring insert

x x	1001	1 x Pt100 in 3-wire circuit
x x	2001	2 x Pt100 in 3-wire circuit

(3) Tolerance class to EN 60751

x x	2	Class A (standard)
x x	3	Class AA (1/3 DIN B)

(4) Protection tube diameter D in mm

x x	6	6 mm
-----	---	------

(5) Fitting length EL in mm (25 ≤ EL ≤ 400)

x x	25	25 mm
x x	50	50 mm
x x	100	100 mm
x x	150	150 mm
x x	...	please specify in plain text (50 mm steps)

(6) Process connection

x x	104	G 1/2 (1/2" pipe) thread
x x	380	G 1/2 (1/2" pipe) thread with CIP-compliant conical seal, with EHEDG certification
x x	601	taper nipple with ring nut DN 10 to DIN 11851 (milk pipe fitting)
x x	604	taper nipple with ring nut DN 25 to DIN 11851 (milk pipe fitting)
x x	605	taper nipple with ring nut DN 32 to DIN 11851 (milk pipe fitting)
x x	611	clamping nipple DN 10/20 to DIN 32676
x x	613	clamping nipple DN 25/40 (1"/1.5") to DIN 32676
x x	616	clamping nipple DN 50 (2") to DIN 32676
x x	617	clamping nipple 2.5" similar to DIN 32676
x x	681	ball weld-in socket with clamping thread
x x	682	weld-in socket with CIP-compliant sealing system
x x	684	Varivent connection DN 15/10 with EHEDG certification
x x	685	Varivent connection DN 32/25 with EHEDG certification
x x	686	Varivent connection DN 50/40 with EHEDG certification
x x	840	ball weld-in pocket (material 316 Ti)
x x	997	JUMO PEKA with EHEDG certification ⁴

(7) Sheath material

x x	24	stainless steel 316 L (Mat. Ref. 1.4404 / 1.4435)
x x	26	stainless steel 316 Ti (Mat. Ref. 1.4571) (on request)

(8) Extra codes

x x	000	no extra code
x x	305	without extension (only for process connection 104 and 380)
x	320	terminal head Form BUZ
x	321	terminal head Form BUZH
x	324	terminal head Form BBKS
x x	330	1 x analog transmitter, output 4 to 20 mA ² , data sheet 70.7030
x x	331	1 x programmable transmitter, output 4 to 20 mA/20 to 4 mA ³ , data sheet 70.7010
x x	333	1 x analog transmitter, output 0 to 10V ² , data sheet 70.7030
x x	365	acceptance test certificate 3.1B EN 10204: insulation resistance
x x	367	acceptance test certificate 3.1B EN 10204: pressure test
x x	368	acceptance test certificate 3.1B EN 10204: leakage test
x x	374	acceptance test certificate 3.1B EN 10204: material
x x	452	parts in contact with the medium electrolytically polished, surface roughness Ra ≤ 0.8 μm (not for process connection 104, 681, 682 and 840)
x x	810	weld-in socket G 1/2 (1/2" pipe) (only for process connection 380 and sheath material 24)

Order code (1) (2) (3) (4) (5) (6) (7) (8) / , ...
Order example 902810/13 - 1001 - 2 - 6 - 100 - 380 - 24 / 000¹

1. List extra codes in sequence, separated by commas.
 2. Specify range in plain text.
 3. Specify range and output signal in plain text.
 4. For matching process connection adapters, see data sheet 40.9711

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14,
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow - Essex CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 63 52 62
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-JUMO
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info@jumo.us
 Internet: www.jumo.us



Stock versions

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	Sales No.
902810/20	- 1001	- 2	- 6	- 25	- 380	- 24	/ 000	90/00466457
902810/20	- 1001	- 2	- 6	- 50	- 380	- 24	/ 000	90/00378357
902810/20	- 1001	- 2	- 6	- 100	- 380	- 24	/ 000	90/00381830
902810/20	- 1001	- 2	- 6	- 25	- 611	- 24	/ 000	90/00407336
902810/20	- 1001	- 2	- 6	- 25	- 613	- 24	/ 000	90/00405849
902810/20	- 1001	- 2	- 6	- 100	- 681	- 24	/ 000	90/00379859